



S.M.C

Armored Telephone Cables CCP-LAP-APE Insulated Steel Wire
 Armored and PE Sheathed Telephone Cables
 (CCP-LAP-A)



Size of Conductor or	No. of Pairs	Insulation Thickness	Nominal Dia. Over Insulation	Nominal Thickness of LAP Sheath(including Aluminum Tape)	Diameter of Steel Wire Armor	Nominal Thickness of Outer Sheath	Max. Overall Diameter of Cable	Approx. cable weight	Standard Packing length	Drum size	Approx. Gross Weight
mm	No.	mm	mm	mm	mm	mm	mm	Kg/Km	Meter ±5%		Kg
0.4	10	0.165	0.73	1.7	1.25	2.5	19	430	1000	D-12	540
	20			1.7	1.25	2.5	21	540	1000	D-12	650
	30			1.7	1.25	2.5	22.5	620	1000	D-14	770
	50			1.7	1.6	2.5	26	870	1000	D-14	1020
	100			1.7	1.6	2.5	30	1180	1000	D-18	1420
	200			1.8	2.0	2.5	37.5	1960	1000	D-19	2280
0.5	10	0.205	0.91	1.7	1.25	2.5	20	500	1000	D-12	610
	20			1.7	1.25	2.5	22.5	620	1000	D-14	770
	30			1.7	1.6	2.5	25	860	1000	D-14	1010
	50			1.7	1.6	2.5	28	1060	1000	D-16	1270
	100			1.7	1.6	2.5	33	1480	1000	D-19	1800
	200			1.8	2.0	2.5	42	2550	1000	D-22	3020
0.65	10	0.255	1.16	1.7	1.25	2.5	21	610	1000	D-12	720
	20			1.7	1.6	2.5	25	880	1000	D-14	1030
	30			1.7	1.6	2.5	28	1020	1000	D-16	1230
	50			1.7	1.6	2.5	31	1330	1000	D-19	1650
	100			1.8	2.0	2.5	40	2200	1000	D-22	2670
	200			2.1	2.0	2.5	49	3460	500	D-19	2050



S.M.C

0.9	10	0.305	1.51	1.7	1.6	2.5	25	850	1000	D-14	1000
	20			1.7	1.6	2.5	30	1110	1000	D-18	1350
	30			1.7	1.6	2.5	33	1370	1000	D-19	1690
	50			1.8	2.0	2.5	39	2090	1000	D-19	2410
	100			2.0	2.0	2.5	47	3220	500	D-19	1930
	200			2.3	2.5	2.5	62	5830	500	D-22	3380