



S.M.C

Telephone Cables CCP-LAP CCP- LAP-SS
 Pre-Insulated and Pre-sheathed Telephone Cables
 (CCP-LAP & CCP-LAP- SS)



Size of Conductor	No of Pairs	Insulation Thickness	Nominal Dia. Over Insulation	CCP-LAP			Self-Supporting Type CCP-LAP-SS					Standard Packaging Length	CCP-LAP		Self Supporting Type	
				Nominal Thickness of LAP Sheath(including Aluminium Tape)	Max Overall Dia of Cable	Approx.Cable weight	Nominal Thickness of LAP Sheath(including Aluminium Tape)	Approx.Ov erall Dia of Cable	Self supporting strand	Approx.C able Height	Approx.C able Weight		Dru m size	Approx.Gr oss weight	Dru m Siz e	Approx.Gr oss weight
mm	No.	mm	mm	mm	mm	Kg/Km	mm	mm	No./mm	mm	Kg/Km	Meter +5%		kg		Kg
0.4	10	0.165	0.73	1.7	11	100	1.7	11	7/1.6	23	280	1000	D-9	160	D-14	420
	20			1.7	13	135	1.7	13	7/1.6	25	315	1000	D-10	200	D-14	460
	30			1.7	14.5	180	1.7	14.5	7/1.6	26.5	365	1000	D-10	240	D-16	570
	50			1.7	17	260	1.7	17	7/1.6	29	450	1000	D-11	360	D-16	660
	100			1.7	21	445	1.7	21	7/1.6	34	625	1000	D-12	560	D-19	950
200				1.8	27.5	835	1.8	27.5	7/2.0	41.5	1155	1000	D-16	1050	D-22	1620
0.5	10	0.205	0.91	1.7	12	125	1.7	12	7/1.6	24	295	1000	D-9	190	D-14	440
	20			1.7	14.5	185	1.7	14.5	7/1.6	26.5	330	1000	D-10	250	D-16	540
	30			1.7	16	240	1.7	16	7/1.6	28	490	1000	D-11	340	D-16	700
	50			1.7	19	365	1.7	19	7/1.6	33.5	550	1000	D-12	480	D-19	870



S.M.C

	100			1.7	24	640	1.7	24	7/2.0	38	930	1000	D-14	790	D-19	1250
	200			1.8	32	1190	1.8	32	7/2.0	46	1575	1000	D-19	1510	D-22	2040
0.65	10	0.255	1.16	1.7	14	160	1.7	14	7/1.6	26	310	1000	D-10	220	D-14	460
	20			1.7	16	255	1.7	16	7/1.6	28	420	1000	D-11	360	D-16	630
	30			1.7	19	360	1.7	19	7/1.6	31	550	1000	D-12	470	D-19	870
	50			1.7	22	550	1.7	22	7/2.0	36	810	1000	D-14	700	D-19	1130
	100			1.8	30	985	1.8	30	7/2.0	45	1365	1000	D-18	1220	D-22	1830
	200			2.1	39	1850	-	-	-	-	-	500	D-16	1140	-	-
0.9	10	0.305	1.51	1.7	16	245	1.7	16	7/1.6	28	430	1000	D-11	350	D-16	640
	20			1.7	21	420	1.7	21	7/2.0	35	700	1000	D-12	530	D-19	1020
	30			1.7	24	590	1.7	24	7/2.0	38	865	1000	D-14	740	D-19	1190
	50			1.8	29	935	1.8	29	7/2.0	44	1290	1000	D-18	1170	D-22	1760
	100			2	37	1705	-	-	-	-	-	500	D-16	1060	-	-
	200			2.3	52	3395	-	-	-	-	-	500	D-22	2170	-	-